

Carbon Dioxide gives fast, safe and effective protection for fires involving electrical equipment and flammable liquids. They are generally suited for use indoors, making them ideal for today's office environments. The cylinders are manufactured from alloy steel, they are highly effective easy to use and leave no messy residue to clear up

### Features

- Available in three sizes, 5lb ,10lb, 15 lb
- CO2 Extinguisher are for class B (flammable liquid) fire and safe for live electrical fires
- Color coded labels for instant type recognition.
- Available for alloy-steel cylinder



**B**Liquids.



**Electrical Equipment**

## BS 5045



### Technical Data

Model	FKC-5	FKC-10	FKC-15
Rating	5 B : C	10 B : C	10 B : C
Outer-Diameter (mm)	125	155	155
Cylinder length (mm)	530	600	780
Cylinder weight (kg)	6.2	9.14	12.48
Gross weight (kg)	8.4	13.64	19.28
Weight of CO2 agent (kg)	2.2	4.5	6.8
Temperature range (f)	-40° to 120°	-40 to 120°	-40 to 120°
Discharge time (second)	9	10	14
Discharge range (feet)	3-8	3-8	3-8
Working pressure (bar)	150	150	150
Test pressure (bar)	250	250	250
Min wall-thickness (mm)	6.6	7	9