

# Fire Hoses

## 2 Premier Extra / Fyrfyter Super



- Bearing IS 636:88 Type A mark
- Wheelmark approved
- Conforming to BS 6391 Type 2, DIN 14811, UL 219, UL 19, EN 14540(2004)
- Jacket made up of 100% polyester for extra strength
- Special quality black EPDM internal rubber lining withstands heat and polluted water
- External coat of synthetic elastomer protects against moisture, fungus, oils, heat & abrasion
- Standard colour: Red
- Options: Green, blue, yellow, orange, black

| Product Code No. | Sizes | Working Pressure<br>PSI/Kg/cm <sup>2</sup> | Burst Pressure<br>PSI/Kg/cm <sup>2</sup> |
|------------------|-------|--|--|
| FH-PE-38         | 1 ½"  | 205/14                                     | 710/50                                   |
| FH-PE-45         | 1 ¾"  | 205/14                                     | 710/50                                   |
| FH-PE-50         | 2"    | 205/14                                     | 710/50                                   |
| FH-PE-63         | 2 ½"  | 175/12                                     | 640/45                                   |
| FH-PE-70         | 2 ¾"  | 175/12                                     | 640/45                                   |
| FH-PE-76         | 3"    | 145/10                                     | 500/35                                   |
| FH-PE-100        | 4"    | 145/10                                     | 500/35                                   |
| FH-PE-125        | 5"    | 100/7                                      | 425/30                                   |
| FH-PE-150        | 6"    | 100/7                                      | 425/30                                   |